



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: RF 1006A CAVITY WAX KIT PART A

Section 01: Chemical product and company identification

Product name..... RF 1006A CAVITY WAX KIT PART A
 Manufactured for..... RUSFRE
 604 McGeachie Drive
 Milton
 Ontario
 L9T 3Y5
 24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.
 Material use..... Rust proofing. This product should not be used for any other purpose other than the ones
 described in this section.
 Chemical family..... Mixture.
 Preparation date..... February 2, 2015.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 2 Reactivity: 0.
 HMIS..... H: 2 F: 2 R: 0.

Section 02: Hazards identification



Signal Word..... DANGER.
 Hazard Classification..... Flammable Aerosol 2. Gas under pressure: Compressed Gas. Aspiration Toxicity 1. STOT
 SE 3.
 Hazard Description..... H223 Flammable aerosol . H280 Contains gas under pressure; may explode if heated.
 H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or
 dizziness.
 Precautionary Statements..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do
 not spray on an open flame or other ignition sources. P251 Do not pierce or burn container,
 even after use. P261 Avoid breathing mists, vapours and sprays. P271 Use only outdoors
 or in a well ventilated area. P280 Wear protective gloves and eye protection.
 Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and
 follow instructions provided by the centre. P304 + P340 - If inhaled remove person to fresh
 air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel
 unwell. P331 Do NOT induce vomiting.
 Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store
 locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C
 / 122°F.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
ODOURLESS MINERAL SPIRITS	64741-65-7	15-40
MINERAL SPIRITS	8052-41-3	10-30
HYDROTREATED HEAVY NAPHTHENIC DISTILLATE	64742-52-5	10-30
CALCIUM CARBONATE	1317-65-3	10-30
CARBON DIOXIDE	124-38-9	1-5

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
 least 15 minutes. Obtain medical attention.

PRODUCT: RF 1006A CAVITY WAX KIT PART A**Section 04: First aid measures**

Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs.

Section 05: Fire fighting measures

Extinguishing media.....	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used.
Hazardous combustion products.....	Oxides of carbon (CO, CO ₂).
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Fire in vicinity poses risk of pressure build-up rupture. In fire situations involving the surrounding area, cool the product down with plenty of water. In case of exothermic decomposition, as indicated by generation of large volumes of smoke, spray immediately and thoroughly with water or pour water on.

Section 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

Section 07: Handling and storage

Handling procedures.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

Section 08: Exposure controls / personal protection

Ingredients	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
ODOURLESS MINERAL SPIRITS	No data	No data	No data	No data	No data	No data
	No data					
MINERAL SPIRITS	525 mg/m ³ 100 ppm	No data	No data	No data	No data	No data
HYDROTREATED HEAVY NAPHTHENIC DISTILLATE	No data	No data	No data	No data	No data	No data
	No data					
CALCIUM CARBONATE	No data	No data	5 mg/m ³	No data	5 mg/m ³	
	No data					
CARBON DIOXIDE	5000 ppm	30000 ppm	5000 ppm	No data	5000 ppm 10 hours STEL 30000 ppm 15 minutes	
	STEL 30000ppm (3%)					

PRODUCT: RF 1006A CAVITY WAX KIT PART A**Section 08: Exposure controls / personal protection**

Protective equipment	
Eye/type.....	Liquid chemical goggles.
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.
Gloves/ type.....	Chemical resistant gloves.
Clothing/type.....	Wear adequate protective clothes.
Footwear/type.....	Safety boots per local regulations.
Other/type.....	Emergency showers and eye wash stations should be available.
Ventilation requirements.....	Local exhaust at points of emission.
Exposure limits	

Section 09: Physical and chemical properties

Physical state.....	Aerosol.
Colour.....	Amber.
Odour.....	Light solvent.
Odour threshold (ppm).....	No data.
Vapour pressure (mm Hg).....	55-65 psig @ 20°C.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Specific gravity.....	No data.
Freezing point (deg C).....	No data.
Solubility.....	Insoluble.
Boiling point (deg C).....	No data.
Evaporation rate.....	> 1.0. (butyl acetate = 1).
Flash point (deg C), method.....	51°C Closed cup.
Auto ignition temperature (deg C).....	450°C.
Upper flammable limit (% vol).....	9.5.
Lower flammable limit (% vol).....	2.1.
Coefficient of water/oil distribution.....	No data.
% Volatile by weight.....	41.36.
VOC.....	No data.
Viscosity.....	No data.

Section 10: Stability and reactivity

Stability.....	Stable at normal temperatures and pressures.
Reactivity conditions.....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Incompatibility.....	Keep away from heat. Incompatible with strong oxidizers.
Hazardous products of decomposition.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).
Hazardous polymerization.....	Hazardous polymerization will not occur.

Section 11: Toxicological information

Ingredients	LC50	LD50
ODOURLESS MINERAL SPIRITS	No data	No data
MINERAL SPIRITS	No data	No data
HYDROTREATED HEAVY NAPHTHENIC DISTILLATE	5 mg/L 4 hours rat	>5000 mg/kg oral rat >5000 mg/kg dermal rabbit
CALCIUM CARBONATE	No data	6450 mg/kg rat oral
CARBON DIOXIDE	No data	No data
Route of entry	Eye contact. Skin contact. Inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	

PRODUCT: RF 1006A CAVITY WAX KIT PART A**Section 11: Toxicological information**

Ingestion..... Slightly toxic. May be harmful if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.
 Carcinogenicity of material..... None known.
 Reproductive effects..... None.
 Toxicological Data

Section 12: Ecological information

Environmental..... Do not allow to enter waters, waste water or soil.
 Biodegradability..... No data.

Section 13: Disposal considerations

Waste disposal..... This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.

Section 14: Transport information

TDG Classification..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
 DOT Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
 IATA Classification (Air)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
 IMDG Classification (Marine)..... UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
 Marine Pollutant..... Potential marine pollutant.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

Section 15: Regulatory information

WHMIS classification..... A. B5. D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous substances None.
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... None.
 EPA hazardous air pollutants (HAPS) 40CFR63 None.
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: Feb02/15



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: RF 1006B CAVITY WAX KIT PART B

Section 01: Chemical product and company identification

Product name..... RF 1006B CAVITY WAX KIT PART B
 Manufactured for..... RUSFRE
 604 McGeachie Drive
 Milton
 Ontario
 L9T 3Y5
 24 hour emergency number..... IN CANADA CALL CANUTEC (613) 996-6666-IN THE UNITED STATES CALL
 CHEMTREC (800) 424-9300.
 Material use..... Rust proofing. This product should not be used for any other purpose other than the ones
 described in this section.
 Chemical family..... Mixture.
 Preparation date..... March 8, 2015.
 Hazard rate
 NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.
 HMIS..... H: 2 F: 4 R: 0.

Section 02: Hazards identification



Signal Word..... DANGER.
 Hazard Classification..... Flammable Aerosol 2. Gas under pressure: Compressed Gas. Aspiration Toxicity 1. Skin
 Irritant 2. STOT SE 3.
 Hazard Description..... H222 Extremely flammable aerosol . H280 Contains gas under pressure; may explode if
 heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 Precautionary Statements..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do
 not spray on an open flame or other ignition sources. P251 Do not pierce or burn container,
 even after use. P261 Avoid breathing mists, vapours and sprays. P264 Wash hands
 thoroughly after handling. P271 Use only outdoors or in a well ventilated area. P280 Wear
 protective gloves and eye protection.
 Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and
 follow instructions provided by the centre. P302 + P352 - If on skin: wash with plenty of
 water. . P304 + P340 - If inhaled remove person to fresh air and keep comfortable for
 breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P321 - Consult with a
 doctor or poison control centre if skin is itchy or a skin rash develops or you feel unwell.
 P331 Do NOT induce vomiting. P332 + P313 - If skin irritation occurs get medical attention
 or advice. P362 + P364 - Take off contaminated clothing and wash before reuse.
 Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store
 locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C
 / 122°F.
 Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Section 03: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS #	Wt. %
HYDROTREATED LIGHT PETROLEUM DISTILLATE	64742-47-8	70-75
PETROLEUM GAS	68476-86-8	25-30

Section 04: First aid measures

Eye contact..... In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at
 least 15 minutes. Obtain medical attention.
 Skin contact..... Remove all contaminated clothing and immediately wash the exposed areas with copious
 amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If
 irritation persists, seek medical attention.

PRODUCT: RF 1006B CAVITY WAX KIT PART B**Section 04: First aid measures**

Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs.

Section 05: Fire fighting measures

Extinguishing media.....	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used.
Hazardous combustion products.....	Oxides of carbon (CO, CO ₂).
Special fire fighting procedures.....	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control. Fire in vicinity poses risk of pressure build-up rupture. In fire situations involving the surrounding area, cool the product down with plenty of water. In case of exothermic decomposition, as indicated by generation of large volumes of smoke, spray immediately and thoroughly with water or pour water on.

Section 06: Accidental release measures

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

Section 07: Handling and storage

Handling procedures.....	Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Employees should wash hands and face before eating or drinking. Keep away from heat, sparks, and open flame.
Storage needs.....	Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

Section 08: Exposure controls / personal protection

Ingredients	ACGIH TLV		OSHA PEL		NIOSH REL
	TWA	STEL	PEL	STEL	
HYDROTREATED LIGHT PETROLEUM DISTILLATE	125 ppm				
PETROLEUM GAS	Not established	Not established	Not established	Not established	Not established
Protective equipment					
Eye/type.....	Liquid chemical goggles.				
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Gloves/ type.....	Chemical resistant gloves.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available.				
Ventilation requirements.....	Local exhaust at points of emission.				
Exposure limits					

Section 09: Physical and chemical properties

Physical state.....	Aerosol.
Colour.....	Clear.
Odour.....	Light solvent.
Odour threshold (ppm).....	No data.

PRODUCT: RF 1006B CAVITY WAX KIT PART B**Section 09: Physical and chemical properties**

Vapour pressure (mm Hg).....	55-65 psig @ 20°C.
Vapour density (air=1).....	>1.
pH.....	Not applicable.
Specific gravity.....	0.717 - 5.98 g/mL.
Freezing point (deg C).....	No data.
Solubility.....	Miscible.
Boiling point (deg C).....	Not available.
Evaporation rate.....	> 1.0. (butyl acetate = 1).
Flash point (deg C), method.....	-104°C.
Auto ignition temperature (deg C).....	Not available.
Upper flammable limit (% vol).....	9.5.
Lower flammable limit (% vol).....	2.1.
Coefficient of water/oil distribution.....	No data.
% Volatile by volume.....	100.
VOC.....	Not available.
Viscosity.....	Not available.

Section 10: Stability and reactivity

Stability.....	Stable at normal temperatures and pressures.
Reactivity conditions.....	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Incompatibility.....	Keep away from heat. Incompatible with strong oxidizers.
Hazardous products of decomposition.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).
Hazardous polymerization.....	Hazardous polymerization will not occur.

Section 11: Toxicological information

Ingredients	LC50	LD50
HYDROTREATED LIGHT PETROLEUM DISTILLATE	NOT INDICATED	NOT INDICATED
PETROLEUM GAS	No data	No data
Route of entry	Eye contact. Skin contact. Inhalation.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal .	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Ingestion.....	Slightly toxic. May be harmful if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Carcinogenicity of material.....	None known.	
Reproductive effects.....	None.	
Toxicological Data		

Section 12: Ecological information

Environmental.....	Do not allow to enter waters, waste water or soil.
Biodegradability.....	No data.

Section 13: Disposal considerations

Waste disposal.....	This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---------------------	--

PRODUCT: RF 1006B CAVITY WAX KIT PART B**Section 14: Transport information**

TDG Classification..... UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
 DOT Classification (Road)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
 IATA Classification (Air)..... UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
 IMDG Classification (Marine)..... UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
 Marine Pollutant..... Potential marine pollutant.
 Proof of Classification..... In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. .

Section 15: Regulatory information

WHMIS classification..... A. B5. D2B.
 CEPA status..... On Domestic Substances List (DSL).
 OSHA..... This product is considered hazardous under the OSHA Hazard Communication Standard.
 SARA Title III
 Section 302 - extremely hazardous None.
 substances
 Section 311/312 - hazard categories..... Immediate health, delayed health, fire hazard.
 Section 313..... None.
 EPA hazardous air pollutants (HAPS) None.
 40CFR63
 TSCA inventory status..... All components are listed.
 California Proposition 65..... This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.

Section 16: Other information

Prepared by: REGULATORY AFFAIRS.
 Telephone number:..... (800) 387-7981.
 Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.
 Preparation date: Mar08/15